

Fasteners

Internal threaded anchor

Material specifications

Coatings	Galvanized
----------	------------



Applications

- Anchorage of medium weight pipeline, ventilation ducts & sprinkler systems

Features & Benefits

- European Technical Approval for non-cracked concrete (Option 7)
- Approved for multiple use for non-structural applications
- Additional safety ensured by fire resistance classification of F120
- Versatile and suitable for attachment with screws or threaded rods
- Quick and easy installation with setting tool and hammer

Select Variant

Article No.	Product Description	Internal Thread	Overall Length (mm)	ETA Option 7	Drill Hole Dia (mm)	Drilling depth (mm)	Usable thread length (mm)	Pack Size (Nos)	Approved load* (kN)	Installation torque (Nm)
Galvanized (vz)										
1740625	FX Drop In Anchor, M6x25	M6	25	●	8	25	8	100	5	4
1740825	FX Drop In Anchor, M8x25	M8	25		10	25	10	100	-	8
1740830	FX Drop In Anchor, M8x30	M8	30	●	10	30	10	100	3.5	8
1740840	FX Drop In Anchor, M8x40	M8	40	●	10	40	12	100	6	8
1741025	FX Drop In Anchor, M10x25	M10	25		12	25	12	50	-	15
1741030	FX Drop In Anchor, M10x30	M10	30	●	12	30	12	50	5.5	15
1741040	FX Drop In Anchor, M10x40	M10	40	●	12	40	15	50	7	15
1741225	FX Drop In Anchor, M12x25	M12	25		15	25	11	50	-	35
1741250	FX Drop In Anchor, M12x50	M12	50	●	15	50	16	50	10	35
1741251	FX Drop In Anchor, M12x50	M12	50		16	50	16	50	-	35
1741665	FX Drop In Anchor, M16x65	M16	65	●	20	65	22	25	12	60

*The admissible loads apply for single anchors in concrete strength class \geq C20/25 (B25 for axially applied tension without the influence of axial and edge spacings. The safety coefficient according to ETA is included.