

## Fasteners

Fastening element for long secured suspensions



### Material specifications

<b>Material</b>	Carbon Steel
<b>Coatings</b>	Galvanized, Hot-Dip Galvanized

### Applications

- Suspending different building services

### Features & Benefits

- High quality 4.8 grade steel rods complying to DIN 976-1

### Select Variant

Article No.		Product Description	Diameter	Length (mm)	Pack Size (Nos)
Galvanized (vz)	Hot Dipped Galvanised (fvz)				
655000	655001	FX Threaded Rod, M8 x 1000mm, DIN 976-1	M8	1000	50
655005	655006	FX Threaded Rod, M8 x 2000mm, DIN 976-1	M8	2000	50
655008	655009	FX Threaded Rod, M8 x 3000mm, DIN 976-1	M8	3000	50
655011	655012	FX Threaded Rod, M10 x 1000mm, DIN 976-1	M10	1000	50
655015	655016	FX Threaded Rod, M10 x 2000mm, DIN 976-1	M10	2000	50
655018	655019	FX Threaded Rod, M10 x 3000mm, DIN 976-1	M10	3000	50
655021	655022	FX Threaded Rod, M12 x 1000mm, DIN 976-1	M12	1000	25
655025	655026	FX Threaded Rod, M12 x 2000mm, DIN 976-1	M12	2000	25
655027	655028	FX Threaded Rod, M12 x 3000mm, DIN 976-1	M12	3000	25
655030	655031	FX Threaded Rod, M16 x 1000mm, DIN 976-1	M16	1000	10
655035	655036	FX Threaded Rod, M16 x 2000mm, DIN 976-1	M16	2000	10
655037	655038	FX Threaded Rod, M16 x 3000mm, DIN 976-1	M16	3000	10

\*Available on request